

## Machine & Working Position Circular LED Lights Specification



Machine & Working position LED lights are suitable for the local lighting, eg. Machine in the production and processing plant, control cabinet, or working position, etc. Based on their high ability on water and dust proofing, the lights with solid shell can be applicable to any harsh environmental conditions. The characteristics of low voltage makes LED can be directly incorporated into the Industrial safety low voltage interface, so it is easy for industrial control

- Fit for small space or local lighting
- Diameter 64 mm
- High power solid state LED array in white models
- 16 to 36V dc operation
- Cabled and quick-disconnect models available
- · Mounts with flex Arm and Right-angle bracket
- IP67
- Before installing the LED lights, must ensure the power off.
- When installing the lights, please accord to the graphic for wiring installation. Must access the anode of 16-36V dc voltage to no.1 pin or hole (when cascaded), and the cathode 16-36V dc voltage to no.3 pin or hole

## **Technical Parameter**

ТҮРЕ	LED-64-12MD
Diameter (mm)	64
Operating Voltage (V)	16-36
Current ( A. 24V)	0.104
Power (W)	4.2W
CCT (K)	5700K
Lumens (Im)	>200
IP	IP67
Operating Temperature	-35°C-60°C<95%RH

## Install schematic diagram is as

