




Rev.	Modify	Date	Signed	Approved

Rev.	Modify	Date	Signed	Approved


Rev.	Modify	Date	Signed	Approved



MALE	PIN #	
	1	+24V
	3	0V DC
	2 / 4	NOT CONN.

FEMALE	PIN #	
	1	+24V
	3	0V DC
	2 / 4	NOT CONN.

! THIS PRODUCT MUST BE ROLLED WITH PLURIBALL FOIL AND MUST BE PACKED IN A SINGLE CARTON BOX COMPLETE OF CAPS AND N°2 FIXING TIE CLIPS ø25mm



! ON THE LAMP (M12 MALE BOTTOM SIDE) MUST BE APPLIED THIS SILVER LABEL



LIGHTING FEATURES	PRODUCT TYPE	INDUSTRIAL LIGHTING
	INDUSTRIAL LIGHTING TYPE	LED LIGHT TUBE WITH M12 CONNECTORS
	TUBE DIAMETER	ø24,8mm
	LIGHTING LENGHT	660mm
	LIGHTCOLOUR	6000K WHITE
	COLOUR RENDERING(RA)	>80
	RATED VOLTAGE	24V DC
	RATED POWER	29W
	LUMINOUS FLUX	1450 lm
	MATERIALS	PLASTIC+ALLUMINIUM
M12 FEATURES	PROTECTION CLASS	IP67
	OPERATING TEMPERATURE	FROM -25°C TO +60°C
	CONNECTOR TYPE	M12 TO PANEL
	MOUNTING TYPE	FRONTAL
	CONTACT TYPE	FEMALE-MALE
	NUMBER OF CONTACTS	n°4
	NUMBER OF CONTACTS CONNECTED	n°2
	HOUSING MATERIAL	BRASS+NICKEL PLATED
	CONNECTOR WITHOUT ANY LOGO	

Designer	SUGLIANI R.	Date	2018-08-30	Tollerance	±0.3	Units:	mm	Series	INDUSTRIAL LIGHTING	Drawing n. 1-1
Approved	CIMMINO L.	Date	2018-08-30	Scale	1:1	Size:	A4	Customer code:		
DESCRIPTION INDUSTRIAL LIGHTING,LED LIGHT TUBE WITH M12 CONNECTORS MALE 4POLES AND FEMALE 4POLES TO PANEL,FRONTAL MOUNTING. 24V DC,LAMP LENGHT=660mm										LED-12FD-T0660-12MD